LGMG SZGAGE II

ELECTRIC MOTOR DRIVE SCISSOR LIFT

- Large lower control panel
- Entire range designed for indoor and outdoor use
- Universal key components
- More convenient to maintain
- Optional lithium battery for the entire product range




LGMG ELECTRIC MOTOR DRIVE SCISSOR LIFT

SPECIFICATIONS

MODELS	S2646E II (S0812E II)
Measurements	Imperial	Metric
Work Height Max.	32'10"	10m
Platform Height-Raised	26'3"	8m
3 Platform Length	7'5"	2.26m
Platform Width	3'8"	1.12m
Overall Length	8'2"	2.49m
3 Overall Width	3'10"	1.18m
Overall Height-Guardrails Up	7'9"	2.36m
6 Overall Height-Guardrails Down	5'1"	1.55m
Extension Deck	2'11"	0.9m
• Wheelbase	6'1"	1.85m
Ground Clearance(Stowed/Raised)	4"/1"	100/20mm
PRODUCTIVITY		
Max. Platform Occupants	2 (in) / 1(out)	
Platform Capacity	990 lbs	450kg
Platform Capacity-Extension Deck	265 lbs	120kg
Drive Height	Full Height	
Gradeability-Stowed	25%	
Min. Turning Radius	8'	2.45m
Raise/Lower Speed	35s / 40s	
Brakes	Front-wheel Brake	
Drive Mode	4x2	
Tire Type	Solid Non-marking	
Tire Size	15"x5"	380x130mm
Ground Pressure, Tyres	167.4 psi	1,154 kPa
POWER		
Power Source	24V (4x6V),240Ah,FLA	
Power Source	24V (4x6V),226Ah,AGM	
HYDRAULIC SYSTEM		
Hydraulic Oil Capacity	4.2gal	16L
WEIGHT		
Machine Weight	5,110 lbs	2,318kg

STANDARD FEATURE	ES
Proportional control	Indoor and outdoor rated
Foldable guardrail	Emergency stop device
Manual brake release	Swing-out component tray
Emergency descent	Tilt alarm with lift cut-out
Pothole guard	Overload sensing system
Self-lock entry gate	Descent alarm with flashing beacon
All motions alarm	Intelligent diagnostic system
Full-height drive	Solid non-marking tires
OPTIONAL	

OPTIONAL	
AC power to platform	Anti-collision protection
Voice alarm system	Maintenance-free battery
Telematics	Biodegradable hydraulic oil



Please contact LGMG or a local dealer for more details.
LGMG reserves the right to change technical data without prior notice. All photos and pictures in this brochure are for promotional purposes only.





